

# Hi-773

## Feature

- 1/3" SONY ExViewHAD II CCD Sensor
- Resolution 700 TV Line
- Min. Illumination(F1.2) 0.01Lux(IR LED Off)
- IR LED Array 2pcs
- IR Distance 25 M
- Lens Fixed 3.6mm (6/8mm Optional)
- Functions AGC, BLC, ATW, Auto Iris
- IP Rank 68
- Power supply DC12V



## Specification



Model	HI-773	IR LED	850nm / 90°, 2pcs Array
Image Sensor	1/3" SONY ExViewHAD II CCD Sensor	IR Visible Distance	25M
Resolution	700TVL	IP Rank	IP68
Min. Illumination	0.01 Lux(IR LED off)	Lens Mount	M12
Scanning Frequency	PAL(15625Hz/50Hz) / NTSC(15734Hz/59.94Hz)	Lens	3.6mm (6.0mm, 8.0mm Optional)
Scanning System	2:1 Interlace	Operating Voltage	DC 12V ±10%
Synchronization	INT	Power Waste	8.5 W (DC12V)
Total number of pixels	1020x596/610K	Operating Temperature / Humidity	-10 °C~+50 °C / 30% - 90%RH
Number of effective pixels	976x582/570K	Storage Temperature / Humidity	-30 °C~+80 °C / 0% - 90%RH
S/N Ratio	> 52 dB (AGC Off)	Video Output Level	1.0 Vp-p 75 Ω
Gain Control	Built-in	Connector	BNC and DC
Backlight Compensation	Built-in	Dimension(mm)	132x77.3x80.4 (without Bracket)
Electronic Noise	2D-DNR	Weight	360 g.
White Balance	ATW		
Shutter Speed	Auto: (1/50(1/60)-120,000Sec)		
Color to Black	Auto (IR Control)		
IR Resection	Built-in		
IRIS Control	Auto IRIS		

## Dimension



\*การบ่งชี้ขนาดของแบบผลิตภัณฑ์ในการประกอบและ ผลิตของประกอบ อ้างอิง โดยไม่บังคับให้ทราบแล้วแต่หน้า

# HI-794

## Feature

- 1/3" SONY Effio E CCD
- Resolution 700 TVL
- Min. illuminations 0.01 Lux/F1.2
- IR LED 10 PC, IR Distance 20-25 Meters  
*(Super Flux IR LEDs for greater distance)*
- Lens 2.8-12mm, Vari-folcal Lens
- OSD Menu Functon
- 12V DC@140mA *(500mA IR LED On)*



## Specification



Model	Hi-794
Sensor	1/3" SONY Effio-E CCD
Max Resolution/ FPS	700 TVL
Min. illumination	0.01Lux / F1.2 IRE40
IR LEDs	10 pc Super Flux IR LED 850nm for 20-25 Meters (65-82 feet)
Lens	2.8-12mm Vari-focal IR Corrected
Angle of view	Maimum: 95.6 °
Video Output	1 x RCA Input / 1 x RCA Output @ 1v Line Level
Electronic Shutter	Auto
Supported Languages	English, Japanese, German, French, Russian, Portuguese, Spanish, Chinese.
Wide Dynamic Range	D-WDR modes, with ATR-EX functions. Clip and Scale user settings.
Digital Noise Reduction	2d
Display Mirror Flip	Horizontal
Privacy Masking	8 User Area defined Windows
Backlight	BLC / HLC
Additional Notes:	Privacy masking has additional setting to mosaic effect.
Power	12v DC @ 140mA (500mA IR LED On)
Temperature	Operating: 14 °F to 131 °F (-10 °C to 55 °C) Storage: -4 °F to 140 °F (-20 °C to 60 °C)
Operating Humidity	10% - 85% RH
Approvals	CE / FCC / RoHS Compliant / IP66 / IK5
Product Dimensions	265.5 x 69 mm ( 10 2/5 x 2 7/8 inch)

# Hi-7351

## Feature

- 1/4" CMOS Super DIS Chip
- Resolution 700 TV Line
- Min. Illumination 0.01 Lux/F1.2
- IR LEDES 24 pcs
- IR Distance 18 M
- Lens Fixed 3.0mm
- IP Rank 66
- Power supply DC12V



## Specification

Model	Hi-7351	IR Distance	15M
Sensor	1/4" CMOS Super DIS Chip	Operation Temperature	-30 °C ~ +60 °C
Pixel	NTSC:720H*480V PAL:720H*576V	Power Supply	DC12V ±10%
Scanning System	PAL/NTSC	Dimension	155(L)*69.4(W)*79(H)/mm
Resolution	700TVL	Gross Weight	380g
Min. Illumination	0.01 Lux/F1.2		
DNR	Auto		
S/N Ratio	≥48dB		
Video Output	1.0Vp-p/75Ω		
AGC	Auto		
White Balance	Auto		
Electronic Shutter	1/50(1/60) ~1/10000 Second		
Gamma Correction	0.45		
Sync. System	Internal		
Lens	3.0mm		
Lens Mount	M12		
ICR	Yes		
IR Led	24pcs		

## Dimension

